






23E2225BS24

DINGS' MOTION  
work order  
DATE REV00

Sticker



4-Ø 5.2 Thru



REVISION

REV.

DATE

DESCRIPTION

DRAWN BY

Notes,  
1.To maximize output force and life of linear actuators,  
radial load on lead screws should be avoided or be kept at a minimum.

|                           |               |
|---------------------------|---------------|
| Motor's phase             | 2             |
| Step angle(±5%)           | 1.8°          |
| Rated current/phase       | 2.5 A(RMS)    |
| Resistance/phase(20°C)    | 2 Ω±10%       |
| Inductance/phase(1V,1kHz) | 5.2 mH±20%    |
| Linear travel per step    | 0.01mm        |
| Lead screw diameter       | Ø 12mm        |
| Lead screw lead           | 2mm           |
| Grade                     | C7 (DY)       |
| Insulation class          | B             |
| Insulation resistance     | 100MΩ(500VDC) |
| Heat rise                 | 80°C          |
| Motor weight              | 0.88 Kg       |


## CUSTOMER

NOTICE TO PERSONS RECEIVING THIS DRAWING

THIS DRAWING IS ONLY CONDITIONALLY ISSUED, AND FOR THE SOLE PURPOSE OF INFORMING LICENSEES AND ASSOCIATE CONTRACTORS OF DINGS' MOTION, AND VENDORS THERETO AND CUSTOMERS THEREOF, RECEIPT OR POCESSION THEREOF DOES NOT CONFER TO TRANSFER ANY RIGHT IN THE SUBJECT MATTER OF THE DRAWING. THE DESIGN, CONSTRUCTION, TECHNICAL INFORMATION AND ALL OTHER SUBJECT MATTER SHOWN AND ASSOCIATE CONTRACTORS OF SAID CORPORATION AND ONLY FOR LICENSED MANUFACTURE, AND BY VENDORS MANUFACTURING FOR SAID CORPORATION AND ONLY FOR LICENSEES AND ASSOCIATECONTRACTORS.

## WIRING CHART

## EXCITATION SEQUENCE



|            |        |   |   |   |
|------------|--------|---|---|---|
| CW         | —————→ |   |   |   |
| Red A+     | +      |   | - |   |
| Red/wht A- | -      |   | + |   |
| Grn B+     |        | + |   | - |
| Grn/wht B- |        | - |   | + |
| CCW        | ←————  |   |   |   |

UNLESS OTHERWISE SPECIFIED ALL  
DIMENSIONS ARE IN MILLIMETERS AND  
TOLERANCES ARE AS BELOW PER ISO2768-cK.

| LINEAR   |      | ANGULAR   |       |
|----------|------|-----------|-------|
| 0 ~ 3    | ±0.2 | 0 ~ 10    | ±15'  |
| 3 ~ 6    | ±0.5 | 10 ~ 50   | ±30'  |
| 6 ~ 30   | ±0.8 | 50 ~ 120  | ±1°   |
| 30 ~ 120 | ±1.5 | 120 ~ 400 | ±1.5° |

DRAWN

DATE

APPRVD

DATE

MODEL

23E2225BS24

**DINGS'**

|       |       |       |        |
|-------|-------|-------|--------|
| SIZE  | A3    | SHEET | 1 OF 1 |
| SCALE | 1 : 1 | REV   | 00     |

